

LAS 2407

ZeroLine®

Compact Design
Stable Temperature

ZeroLine®

ZeroLine® is a registered trademark of Virutex S.A.



NEU

ZeroLine® technology

The edge banding machines with hot air technology fuse the edge to the panel, providing a perfect finish and seamless joint.

Portable edgebander

Compact design Portable Edgebanding machine with ZeroLine® technology by hot air. Thanks to this technology the banding between the panel and the tape is practically perfect, with a seamless joint. The result is an edgebanding of high quality.

Perfect finishing on straight, round, shaped and inclined panels. Very practical for small or medium manufacturing series due to its easy operation and fast adjustment.

For PVC & ABS tapes with coextruded or postprocessed active layer, so it is not necessary to clean a glue tank.

For tapes up to 3 mm thickness. It is possible to band acrylic and lacquered boards.

The LAS2407 works with low pressure air. It does not need a high performance compressed air system.

With light indicator of optimal working temperature reached. Equipped with roller holder.

Glue line with other edgebanding technologies.



Seamless joint with ZeroLine® technology.



SCHUGOMA®
SYSTEM

Perfect fusion of the tape and panel.

With a 40% higher adhesion than conventional hot-melt coating

LAS 2407

ZeroLine®

ZeroLine®

ZeroLine® is a registered trademark of Virutex S.A.

Compact design Portable Edgebanding machine with ZeroLine® technology by hot air. The edge banding machines with hot air technology fuse the edge to the panel, providing a perfect finish and seamless joint.



Perfect finishing on straight, round, shaped and inclined panels (0° - 50°)



Automatic tape positioning

With assisted tape feeding and electronic speed control

Equipped with roller holder

Specifications

Rated input Power: 3400 W
Tape height: 10 - 65 mm
Turntable: 0° - 50°
Tape thickness: 0.8 - 2.0 mm
Inner Radi: 12 mm
Heating time: 240 s (4 min)

Temperature max.: 370° C
Speed: 1.0 - 3.3 m/min
Weight: 11.5 kg
Size (L x W x H): 230x212x360mm
Air connection: 6 bar

Specifications subject to change without previous notice.

With extra strong fixing system



Schugoma System GmbH
Im Schlahbruch 15, D-59872 Meschede
Tel.: +49 (0) 291 902 205-0 | info@schugoma.de | www.schugoma.de